



EAS LIFT

HAND CONTROLLED
PERMANENT
MAGNET LIFTERS



EAS presents the EAS Lift; hand controlled permanent magnet lifters for a wide range of purposes.

www.easlift.com

EAS Lift

Hand controlled permanent magnet lifters



The EAS Lift utilizes state of art technology to make a powerful, lightweight permanent lifting magnet. Our exclusive Test Talon® feature allows an operator to safely test load feasibility and a deep "V" notch between the pole shoes allows greater stability when lifting round stock.

Test Talon®
Safety Feature

EAS shares your concerns for safety in the workplace.

That's why the EAS Lift is designed with the exclusive TestTalon®. By simply moving the handle to the "Test" position, the operator can undertake a trial lift. If the EAS Lift successfully lifts the load with the TestTalon® engaged, the handle can be moved to the "On" position and the operator can continue the lift confident that the load is within the rated capacity of the EAS Lift.

Product specifications (Metric Data)									
Safe Working Loads (SWL)*						Product Dimensions			
Model Number	Flat Capacity (kg)	Round Capacity (kg/range mm)	Min Contact Area (mm)	Min Load Thickness (mm)	Max Load Length (m)	Unit Weight (kg)	L (mm)	W (mm)	H (mm)
EL-M125	125	N/A	103x50	20	1,2	4	120	125	120
EL-M275	275	140/100-300	103x100	20	1,8	7	165	125	120
EL-M550	550	275/100-300	212x103	20	3	13	280	125	120
EL-M1100	1100	550/150-500	284x151	30	3	52	370	190	190
EL-M2200	2200	1100/150-500	568x151	30	3,6	95	650	190	190

Product specifications (Imperial Data)									
Safe Working Loads (SWL)*						Product Dimensions			
Model Number	Flat Capacity (lbs)	Round Capacity (lbs/range inch)	Min Contact Area (in)	Min Load Thickness (in)	Max Load Length (ft)	Unit Weight (lbs)	L (in)	W (in)	H (in)
EL-250	250	N/A	4x2	¾	4	10	4½	5	4½
EL-600	600	300/4-12	4x4	¾	6	16	6½	5	4½
EL-1200	1200	600/4-12	8,5x4	¾	10	30	10½	5	4½
EL-2500	2500	1250/6-20	11x6	1¼	10	115	14½	7½	7½
EL-5000	5000	6/20/2500	22x6	1¼	12	210	25½	7½	7½

The EAS Lift is available via the EAS Shop on internet. There you can find all the types and prices and you can order your own EAS Lift permanent magnet lifters.

For more information about this product you can contact EAS in Holland or our local dealers (see www.easchangesystems.com under 'contact').

- Test load is approximately three times rated load.
- Variation on round capacities are available as a special order
- * - Never exceed SWL (Safe Working LOAD) and always observe safe lifting practices.
- The Pole/Workpiece contact area is absolute minimum permissible.
- Test load was based on a machined, flat, mild steel of greater than or equal to the minimum thickness stated.
- 3 year warranty